

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As used on Label and List)

LIGHT MINERAL OIL

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name: Geritrex Corp.

Address (Number, Street, City, State, and ZIP Code)

144 Kingsbridge Rd. East

Mount Vernon, NY 10550

Emergency Telephone Number: (914) 668-4003

Telephone Number for Information: (914) 668-4003

Date Prepared: 05/18/99

Signature of Preparer (optional Charles Ovaiwe)

Section II – Hazardous Ingredients/Identity information

Hazardous Components (Specific Chemical Identity; Common Names(s) OSHA PEL ACGIH TLV Other Limits % (optional) Recommended

MINERAL OIL

Section III – Physical/Chemical Characteristics

Boiling Point:	300-305°C	Specific Gravity (H2O = 1)	0.842
Vapor Pressure (mm Hg.)	<1	Melting Point: Not Available	N/A
Vapor Density (AIR = 1)	>1.0	Evaporation Rate (Butyl Acetate =1)	N/A

Solubility in water: Insoluble in water, soluble in hydrocarbons

Appearance and Odor: Transparent, odorless liquid

Section IV – Fire and Explosion Hazard Data

Flash Point (method Used): 335 F	Flammable Limits: No data	LEL: NONE	UEL : NONE
Extinguishing media: Use dry chemical foam, Carbon Dioxide or water fog			
Special Fire Fighting Procedures: Do not use stream of water as this will scatter liquid and spread fire.			
Unusual Fire and Explosion Hazards: Firefighters must use full bunker gear including NIOSH-approved positive pressure self contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.			

Section V – Reactivity Data

Stability:	Unstable:		Conditions to Avoid: None
	Stable:	X	

*Incompatibility (Materials to Avoid): Strong Oxidizers

Hazardous Decomposition or By products:

Hazardous Polymerization:	May Occur:	X	Conditions to Avoid: temp of 120 F
	Will Not Occur:		

Section VI – Health Hazard Data

Route(s) of Entry:	Inhalation? None	Skin? None	Ingestion? Laxative Effect
Health Hazards (Acute and Chronic): None			

Carcinogenicity: N/A	NTP N/A	IARC Monographs N/A	OSHA Regulated N/A
----------------------	---------	---------------------	--------------------

Signs and Symptoms of Exposure: Indigestion, nausea, vomiting and diarrhea

Medical Conditions Generally Aggravated by Exposure: N/A

Emergency and First Aid Procedures: N/A

Section VII – Precaution for Safe Handling and Use

Steps to be Taken in Case Material Is Released or Spilled: Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazards; do not walk through spilled material. Stop leak if you can do so without risk. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste Containers for later disposal. Contain large spills to maximize product recovery or disposal. Prevent entry into waterways or sewers. In urban area, cleanup spills as soon as possible. In natural environments, seek cleanup advice from specialists to minimize physical habitat damage. This material will float on water. Absorbent pads and similar materials can be used. Comply with all laws and regulations.

Waste Disposal Method:
Conditions of use may cause this material to become a “hazardous waste”, as defined by the federal or state regulations
Treatment, storage and disposal of waste material must be conducted in accordance with RCRA regulations. State and/or local regulations may be more restrictive.

Precautions to Be Taken in Handling and Storing:
Avoid water contamination and extreme temperatures to minimize production degradation. Empty containers may contain product residue that can ignite with explosive force. Do not pressurize, cut, weld, braze solder, drill, grind, or expose containers to flames, sparks, heat or other potential ignition sources. Keep container closed. Do Not store with strong oxidizing agents. Do Not store at temperatures above 120 degrees F or in direct sunlight for extended periods of time. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residue of this product.

Other Precautions: Store at room temperature

Section VIII – Control Measures

Respiratory Protection (Specify Type); Not required for normal use

Local Exhaust: N/A	Special: N/A
Mechanical (General): N/A	Other: N/A

Protective Gloves: N/A | Eye Protection: N/A

Other Protective Clothing or Equipment: Not required under conditions of normal use.

Work/Hygienic Practices: Normal handling

THE INFORMATION AND RECOMMENDATIONS IN THIS DATA SHEET ARE BELIEVED TO BE CORRECT AND RELIABLE. HOWEVER THE DATA IS OFFERED FOR CONSIDERATION AND VERIFICATION BY THE USER AND Geritrex Corp. OFFERS NO GUARANTEE, WARRANT OR REPRESENTATION AS TO THE ACCURACY OR COMPLETENESS OF THE DATA

